RELIANCE fall protection

4104T

External

Shock Absorber

Dyneema® Webbing

Pelican Hook

(other hooks available)

Durable, lightweight

plastic housing

4007-65 Connector attaches two units to

dorsal webbing on

harness - not to

Harness D-Ring.

Product Data Sheet

StopLite II® Self Retracting Lifelines

The StopLite II® Personal SRL is an update to our original StopLite® designed to reduce weight and improve performance. StopLite II® offers an unsurpassed level of safety, security and performance which challenge other products to keep up. This product exceeds ANSI and OSHA requirements by leaps and bounds and is manufactured using only the highest quality materials.

- High capacity energy absorber for improved performance
- Average arrest distances 10 20% less than standard limits
- Webbing strength exceeds standard minimums by >30%
- FailSafe[™] cam-driven locking design guarantees locking engagements and is superior to centrifugal mechanisms

The StopLite II® can be attached quickly and easily to the back of a full body harness utilizing the Reliance SRL connector. Use of the connector allows for the attachment of either one or two StopLite II® devices without sacrificing the availability of the back D-ring. These products may also be used in traditional applications, suspended from overhead anchorages in smaller work-spaces.

Product Features

- External, High-Capacity Energy Absorber
- Lighter Weight and Extremely Durable
- High-Strength Dyneema® webbing
- Four connector options
- Available in Singles and Twins
- Meets or exceeds OSHA and ANSI Z359.14 requirements.

Specifications

• Working Length: 7 - 10 feet (2.13 - 3.05 m)

Height: 4.125 inches (10.4cm)
Width: 3.5 inches (8.9cm)
Depth: 2.75 inches (7.0cm)
Weight: 2.9 - 7.8 lbs

Weight. 2.7-7.0 (b)

Capacity: One Worker up to 400 lbs (181kg) (worker, tools,

equipment & clothing)

Available Models				
Part #	Description	Length (ft)	Weight (lbs)	SRL Connector (4007-65)
4103-1	Single, Steelhead™ Snap Hook (Tie-Back)	10'	3.15	No
4103T	Twin, Steelhead™ Snap Hook (Tie-Back)	10'	6.60	Yes
4104-1	Single, Pelican Snap Hook	7'	2.90	No
4104T	Twin, Pelican Snap Hook	7'	6.00	Yes
4105-1	Single, Steel Rebar Hook	7'	3.75	No
4105T	Twin, Steel Rebar Hook	7'	7.80	Yes
4106-1	Single, Aluminum Rebar Hook	7'	3.40	No
4106T	Twin, Aluminum Rebar Hook	7'	7.10	Yes